

MASTER GEAR 1.0


	LOAD STROKE	FOOT HYDRAULIC	ELECTRO HYDRAULIC
	PRECISION STROKE	FOOT HYDRAULIC	HAND HYDRAULIC
	CAPACITY	1000 KG	2000 KG
	STROKE	1330 MM	1000 MM
A	LENGTH	1260 MM	1700 MM
В	WIDTH	720 MM	800 MM
С	HEIGHT MIN.	635 MM	730 MM
	HEIGHT MAX.	1965 MM	1730 MM
	WEIGHT	290 KG	550 KG
	ADJUSTMENT CAPACITY	± 20 MM	± 20 MM
	INCLINE CAPACITY	+ 2 °	+ 2 °

Universally Adjustable Due to construction. modern vehicle aggregates can only be removed and/or mounted via the underside of the vehicle. The new aggregate platform lifts of the Master Gear series are ideally suited to this field of application.

The Master Gear excels itself thanks to the manifold adjustable and tiltable supporting platform VarioDesk. Even the mounting of complete exhaust systems can be easily carried out by one person alone.



MASTER GEAR 2.0



■ 1. LOCATION HOLES Additional, vehicle-specified tools, can be firmly fastened to the platform surface by means of the continuous location hole matrix. ■ 2. SAFETY The generous base of the Master Gear lifting platform ensures high stability and therefore enables safe and exact work. ■ 3. COMPLETELY FOOT-OPERATED The integrated sink brake valve allows an exact control of the lowering speed. The load stroke is foot-hydraulic. ■ 4. FULLY MOBILE Generously sized rollers - 2 fixed, 2 swivelling with integrated locking brakes - provide mobility at work. . ■ 5. VARIODESK The supporting platform surface of the Master Gear is not only extensive but also offers diverse adjustment possibilities due to a flexibility of ± 20 mm in xand y-axle and a tilting angle of ± 2°.



BlitzRotary GmbH Hüfinger Straße 55 D-78199 Bräunlingen Telefon +49.771.9233.0 Telefax +49.771.9233.99 www.blitzrotary.com

A DOVER COMPANY





