


# TANK FOR DIESEL TRANSPORT “Caddy”



**55 I**



**110 I**

Ref.	Descrip.	Flow rate for 100 revolutions		Width	Depth	Height	Nozzle	Weight	Packaging
		I	USG	mm	mm	mm		kg	mm

<b>090-6055-M00</b>	Caddy 55 I	<b>38</b>	10	460	360	900	Manual	8,00	1000X500X500
<b>090-6110-M00</b>	Caddy 110 I	<b>38</b>	10	460	440	1100	Manual	12,00	1200X500X500

## TANK FOR DIESEL TRANSPORT “Caddy”

Rigid polyethylene tank for diesel transport for private and professional use in total exemption for ADR (see ADR Regulation at page 180), perfect for refuelling of small operative vehicles, light-duty or recreational vehicles. It is equipped with run-flat wheels and suitable for moving on any ground. They have compact dimension for easy moving. Every tank can be filled vertically or horizontally, with the same fuel quantity. Provided with nozzle holder bracket, sphere relief valve with swiveling joint, filling plug with anti-spill vent valve.

### “Caddy” series composed by:



**Art. 090-6055-M00** Wheeled Caddy Tank 55 l diesel

**Art. 090-6110-M00** Wheeled Caddy Tank 110 l diesel



**Art. 027-3720-000** Alluminium manual rotary pump



**Art. 908-0500-040** Antistatic rubber hose Ø 20 mm 4 m lenght



**Art. 093-5200-000** Manual nozzle “MC 80” Flow rate 80 l/min